

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



534811

(43) International Publication Date
10 June 2004 (10.06.2004)

PCT

(10) International Publication Number
WO 2004/048100 A1

(51) International Patent Classification⁷: **B41J 2/05, 2/16**

(21) International Application Number:
PCT/AU2003/001502

(22) International Filing Date:
17 November 2003 (17.11.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/303,352 23 November 2002 (23.11.2002) US

(71) Applicant (for all designated States except US): **SILVERBROOK RESEARCH PTY LTD [AU/AU]**; 393 Darling Street, Balmain, New South Wales, 2041, (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **SILVERBROOK, Kia [AU/AU]**; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).

(74) Agent: **SILVERBROOK, Kia**; Silverbrook Research Pty Ltd, 393 Darling Street, Balmain, New South Wales 2041 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: SELF-COOLING THERMAL INK JET PRINTHEAD



(57) Abstract: There is disclosed an ink jet printhead which comprises a plurality of nozzles (3) and one or more heater elements (10) corresponding to each nozzle. Each heater element is configured to heat a bubble forming liquid in the printhead to a temperature above its boiling point to form a gas bubble (12) therein. The generation of the bubble causes the ejection of a drop (16) of an ejectable liquid (such as ink) through the respective corresponding nozzle, to effect printing. Each heater element is configured such that the energy applied to it to heat the bubble forming liquid to cause the ejection of a drop is less than that required to heat a volume of the ejectable liquid equal to the volume of such a drop, from an ambient temperature (being the temperature at which the bubble forming liquid enters the printhead) to the temperature of such a drop when it is ejected. The printhead thus has a self-cooling function.